

701, Rustomjee Aspiree, Bhanu Shankar Yagnik Marg, Off Eastern Express Highway, Sion (E), Mumbai - 400 022. Tel.: 022-6149 7000

# N N 2021 \_\_\_\_\_ **LIGHTING**







**TO THE PERFECT AND INCREDIBLE LED LIGHTING SOLUTIONS** 

# **OPEN THE WORLD**



# SPREADING LIGHT. ILLUMINATING LIVES.

At Bajaj Electricals, we have been on a perpetual journey towards building the future and opening your world to new possibilities and new ways of living. Through innovation, technology and nuanced understanding of consumers, our new-age lighting solutions are playing a meaningful role in the everyday lives of Indian families.

In the past few decades, we have seen a rapid acceleration of globalisation due to the growth in international trade and technological advancements. Over the years, we, at Bajaj Electricals, have been meeting these demands and creating an impact by expanding our horizons through a host of innovative indoor and outdoor lighting solutions. Our aim is to continually provide you technology-led solutions that suit your modern-day needs.


We have strengthened our position in the global lighting market by offering functional and efficient indoor, consumer-centric lighting solutions. Our presence in the outdoor lighting segment like sports lighting and architectural lighting is also noteworthy. We are constantly evolving, innovating and creating energy efficient spaces and smart cities across the world. For us, every day is about transforming the future by spreading light and illuminating millions of lives through our diverse range of solutions.



# NABL ACCREDITED PHOTOMETRIC LABORATORY

# LANDMARKS ILLUMINATED







CHHATRAPATI SHIVAJI MAHARAJ TERMINUS, MUMBAI, MAHARASHTRA

BANDRA-WORLI SEA LINK BRIDGE, MUMBAI, MAHARASHTRA

BOGIBEEL RAIL ROAD BRIDGE, DIBRUGARH, ASSAM



# THE PERFECT AND INCREDIBLE LIGHTING SOLUTIONS PARTNER

We are known for our pioneering work in the world of lighting solutions. As a legacy brand with more than four decades of experience, we are on a continuous mission of learning and growing with time. It is our deep understanding of our consumers and the industry that helps us build smart and contemporary solutions which suit your modern lifestyle. Our innovative and efficient residential lighting solutions go to show our promise of 'open new life.'

Our indoor and outdoor lighting solutions address your modern-day needs and are customised to bring convenience and ease in your life. The Sunshine CRI Plus LED range gives a lighting experience similar to natural light while the smart AWE bulb lets you switch and adjust between different wellness-centric lighting modes with just a touch of your finger. Our energy-efficient Hi5 & Ivora Plus LED range imbibes the spirit of energy consciousness and our Inverter LED products deliver convenience by functioning smoothly in alternate situations. These, along with our latest additions to the LED lighting range such as Recessed lighting solutions, Portable lighting solutions and accessories, and Outdoor luminaires with IP65 protection, are a testimony to our deep-rooted consumer understanding.

We promise to continue our journey of developing perfect and incredible Bajaj LED lighting solutions that enhance your space and help you build a brighter tomorrow. We will always work towards providing you the best in-class solutions and producing efficient lighting that complements your lifestyle.

# **FEATURES**





<u>//</u>

NO. OF LED

4



LIGHT-WEIGHT LI-ION BATTERY





HEAVY DUTY RECHARGEABLE BATTERY







FIRE RETARDANT HOUSING



SHIELD<sup>\$</sup>

BEAM ANGLE 1800

FIRE RETARDANT CABLE



FEATHER TOUCH OPERATION



PB SWITCH CONTACT











# SPECTRUM BASED LIGHTING HAVING WAVELENGTH OF 585-590 NM



MULTI-WAY USAGE







"Image is for representation purpose only. Actual product may vary. | ""Burning life under normal working condition.

# **BAJAJ AWE BULB'S PERFECT AND INCREDIBLE LIGHTING**



Install the Bajaj 'AWE' Lamp by holding just the lamp housing into the light socket



Now, switch 'ON' the electrical power and the 'AWE' lamp will be turned on




Set the ambience right with the perfect light from Bajaj AWE. Select from the 12 diverse and delightful pre-defined settings, that let you set your desired ambience at a click



Revel in the splash of colours, choose from a plethora of 16 million colours and light up your room with the Colour Wheel from Bajaj AWE

SUNSHINE CRI PLUS LED RANGE





Presenting the Sunshine CRI Plus range of high CRI LEDs from the house of Bajaj. It is designed on the principle of Colour Rendering Index, which is a prime factor in measuring the ability of the light source to reveal the TRUE COLOURS of the objects in comparison with natural light.

JUST LIKE NATURAL LIGHT

While most LEDs operate at a CRI of 70, Bajaj's Sunshine CRI Plus LEDs have a CRI of 90+, which makes objects appear just as they look under natural light.



# SUNSHINE CRI PLUS LED BATTEN 20W

- High Colour Rendering Index (CRI>90)
- Lumen efficacy of 100 Lm/W in CDL variant
- Designed to deliver glare-free light
- 2.5 kV voltage surge protection
- Power factor > 0.9
- Elegant endcaps with engineering plastic housing
- Available in CDL (6500K)





"Image is for representation purpose only. Actual product may vary. | \*Nearest Incandescent bulb equivalent measure according to IEC 60064, nearest CFL bulb equivalent measure according to IEC 60969, compared to T8 FTL 36w fitting". | ""Burning life under normal working condition.



VSP TECHNOLOGY

# SUNSHINE CRI PLUS LED LAMP 9W/12W

- High Colour Rendering Index (CRI>90)
- BEE 3-Star rated, energy-efficient product
- Lumen efficacy of 90 Lm/W
- 3.5 kV Voltage surge protection
- Beam angle 120°
- Available in CDL (6500K)



# SUNSHINE CRI PLUS LED COB DOWNLIGHT 12W

- High Colour Rendering Index (CRI>90)
- Lumen efficacy of 100 Lm/W
- 2.5 kV voltage surge protection
- Power factor > 0.9
- Housing made from powder coated die-cast aluminium with swivel operation
- Specially designed heat sink for enhanced life
- Available in day light (5000K)



"Image is for representation purpose only. Actual product may vary. | Shields from life threatening Aedes aegypti mosquitoes (89% & 80% in light & dark condition respectively) causing Dengue Fever, from Culex quinquefasciatus mosquitoes (88% & 73% in light & dark condition respectively) causing Arbovirus infections and from Housefly Musca domestica (78% & 90% in light & dark condition respectively), when the Lamp illuminates the insect entry path . Tested effectiveness both in dark & illuminated background in 30m<sup>3</sup> test chamber. | #Burning life under normal working condition.

# **EFFICIENCY CERTIFICATE**

# **HIGH LUMEN EFFICACY LED RANGE**



HIGH LUMEN EFFICACY



# SOOTHING 25,000#\* HOURS

# IVORA<sup>®</sup> LED BATTEN 16W (1800 Lm)

- Lumen efficacy of >110 Lm/W in CDL variant
- 2.5kV voltage surge protection
- Power factor >0.9

NEW

- Housing made from engineering plastic
- Designed to deliver glare-free light
- Available in CDL (6500K)





<sup>#</sup>Image is for representation purpose only. Actual product may vary. | \*Nearest Incandescent bulb equivalent measure according to IEC 60064, nearest CFL bulb equivalent measure according to IEC 60969, compared to T8 FTL 36w fitting". | <sup>##</sup>Burning life under normal working condition.



POWER

# IVORA<sup>®</sup> PLUS LED BATTEN 18W(2000 Lm)

- Lumen efficacy of > 110 Lm/W in CDL variant
- 2.5kV voltage surge protection
- Power factor > 0.9
- Housing made from engineering plastic
- Designed to deliver glare-free light
- Available in CDL (6500K)





# IVORA<sup>®</sup> PLUS LED PANELS

- Lumen efficacy of >110 Lm/W in CDL variant
- Back-lit technology
- 2.5 kV voltage surge protection
- Power factor >0.9
- Housing made from engineering plastic
- Designed to deliver glare-free light
- Available in CDL (6500K), round & square profile, in 6W, 12W & 18W

LED BACK UP SERIES



LEDZ INVERTER









(2.5 KV VSP TECHNOLOGY

- **:0%**\* POWER SAVING

CFL bulb equivalent measure according to IEC 60969, compared to T8 FTL 36w fitting", | #"Burning life under normal working condition.

# **LED BACK UP SERIES**



**NEW** 

• Back up time of up to 3 hrs.

• Auto cut-off after full battery charging

07 BAJA

• Regular operation lumen of 1800 Lm & back up lumen of 300 Lm

07

- 2.5kV voltage surge protection
- Available in CDL (6500K) only
- Available in 20W only







15,000##

HOURS

MOVEMENT

POWER SAVING

# IVORA<sup>®</sup> PLUS LED LINEAR LAMP

- Unique angular movement with wider spread of light
- Lumen efficacy of 105 Lm/W in CDL variant
- 2.5 kV voltage surge protection
- Available in CDL (6500K) only
- Wide operating voltage range 120-300V AC UNIQUE ANGULAR
  - Available in 10W, 14W & 18W CDL B22 only



IVORA<sup>®</sup> LINEAR **DECO LAMP** 

- Unique angular movement with wider light spread
- 2.5 kV voltage surge protection
- Wide operating voltage range 120V-300V AC
- Available in 4 colours red, green, blue and yellow
- Available in 5W

VSP TECHNOLOGY UNIQUE ANGULAR MOVEMENT 15,000## HOURS POWER ECO-FRIENDLY SAVING LIGHT

# IVORA<sup>®</sup> LED HW LAMP

- Lumen efficacy of 90 Lm/W
- 3 kV voltage surge protection
- Beam angle > 180°
- CRI > 80
- Power factor > 0.9
- Available in CDL (6500K)
- Suitable for indoor applications only
- Available in 30W, 40W & 50W
- Available in B22 and E27 cap type







- Operating voltage: 220V-240V, 50Hz
- Cap type: E14
- Application in chandeliers & decorative fixtures

NEW

• Lumen: 80 Lm





- CFL bulb equivalent measure according to IEC 60969, compared to T8 FTL 36w fitting". | #Burning life under normal working condition. —





# LEDZ PLUS / LEDZ LED LAMP

- BEE star-rated energy efficient LED retrofit bulb
- Lumen Efficacy of >105 Lm/W for CDL B22 & > 90 Lm/W for other variants
- 3.5 kV voltage surge protection
- Beam angle > 120°
- CRI > 80
- Available in CDL (6500K), WDL (3000K)
- Available in B22 & E27 base caps
- Available in 3W, 5W, 7W, 9W, 12W, 15W, 18W & 23W






ECO-FRIENDLY

LIGHT

# LEDZ PING PONG

- Wide operating voltage range 160-260V AC
- 1.5 kV voltage surge protection
- Available in 7 colours as white, red, blue, green, yellow, pink & orange
- Unbreakable



# IVORA<sup>®</sup> DELUXE LED BATTEN

#### COMPACT BATTEN









ECO-FRIENDLY LIGHT



SOOTHING LIGHT

# IVORA<sup>®</sup> DELUXE LED BATTEN

- Lumen efficacy of 100 Lm/W in CDL variant
- 2.5 kV voltage surge protection
- Power factor > 0.9
- Decorative dual coloured endcaps mounted on extruded aluminium housing
- Designed to deliver glare-free light
- Available in CDL (6500K)
- Available in 20W (2ft.) & 36W (4ft.)





VSP TECHNOLOGY

NEW

# IVORA<sup>®</sup> LED BATTEN

- Lumen efficacy of 100 Lm/W
- 3.5kV voltage surge protection
- Power factor > 0.9
- Designed to deliver glare-free light
- With housing made of engineering plastic
- Available in CDL (6500K) • Available in 10W & 20W
- SOOTHING LIGHT



GLOWING END CAP



- 3 mode operations of decorative, regular and night lamp
- Lumen efficacy of 100 Lm/W
- 2.5kV voltage surge protection
- Power factor > 0.9
- Designed to deliver glare free light
- Available in CDL (6500K) for regular and blue colour light for end cap
- Available in 20W





# IVORA<sup>®</sup> LED BATTEN 25W

- Lumen efficacy of 100 Lm/W in CDL variant
- 2.5kV voltage surge protection
- Power factor > 0.9
- With square-shaped housing made
- from engineering plastic
  - Designed to deliver glare-free light
  - Available in CDL (6500K) & WDL (3000K)

SOOTHING LIGHT





- Lumen efficacy of 100 Lm/W in CDL variant
- 2.5 kV voltage surge protection
- Power factor > 0.9
- Elegant endcaps with housing made from engineering plastic
- Designed to deliver glare-free light
- Available in CDL (6500K) & WDL (3000K)
- Available in 5W, 10W & 20W







# **LED RETROBAR 18W**

- Lumen efficacy of 100 Lm/W
- 2.5 kV voltage surge protection
- Power factor > 0.9
- Polycarbonate housing
- Designed to deliver glare-free light
- Easy installation in T8/T12 fixtures
- Available in CDL (6500K)
- 25,000## HOURS

<sup>#</sup>Image is for representation purpose only. Actual product may vary. | \*Nearest Incandescent bulb equivalent measure according to IEC 60064, nearest - CFL bulb equivalent measure according to IEC 60969, compared to T8 FTL 36w fitting". | #"Burning life under normal working condition. —

VSP TECHNOLOGY



# **LED BATTEN 18W**

- Lumen efficacy of 100 Lm/W in CDL variant
- 2.5 kV voltage surge protection
- Power factor > 0.9
- Decorative dual coloured endcaps with powder coated extruded aluminium housing
- Designed to deliver glare-free light
- Available in CDL (6500K)









# INDOOR LUMINAIRES



00

# IVORA<sup>®</sup> COB DOWNLIGHT RANGE

NEW

COB LED





WIDE OPERATING VOLTAGE



COB TECHNOLOGY



HOURS



# IVORA<sup>®</sup> LED COB DOWNLIGHT

- Lumen efficacy of 100 Lm/W in CDL variant
- 2.5 kV voltage surge protection
- Power factor > 0.9
- Housing made from powder coated die-cast
   aluminium with swivel operation
- Specially designed heat sink for enhanced life
- Available in CDL (6000K) & WDL (3000K)
- Available in 3W, 6W, 9W, 12W & 15W

VSP TECHNOLOGY

# SURFACE RIM FOR IVORA<sup>®</sup> LED PANEL RANGE

- Made from engineering plastic
- Modular design to help convert from
  recessed fitting to surface mounted fitting
- To be used with Ivora LED panels
- Available in round & square profile
- Available in 4 sizes, suitable for 3W, 6W, 9W, 12W, 15W and 18W

<sup>#</sup>Image is for representation purpose only. Actual product may vary. | \*Nearest Incandescent bulb equivalent measure according to IEC 60064, nearest CFL bulb equivalent measure according to IEC 60969, compared to T8 FTL 36w fitting". | <sup>##</sup>Burning life under normal working condition.





# IVORA<sup>®</sup> LED PANELS

- Edge-lit technology for glare-free light
- 2.5 kV voltage surge protection
- Housing made from engineering plastic with inbuilt driver
- Power factor > 0.9
- Wide operating voltage range 100-300V AC
- Unique design enabled by a separate modular surface rim to convert from recessed to surface mounting
- Available in CDL (6000K), NDL (4000K) & WDL (3000K)
- Available in round & square profile
- Available in 3W, 6W, 9W, 12W, 15W & 18W











# IVORA<sup>®</sup> LED CEILING LIGHT

- Elegant design to deliver wide spread glare-free light
- Lumen efficacy of 85 Lm/W in CDL variant
- 2.5 kV voltage surge protection
- Power factor > 0.9
- Housing made of pre-coated CRCA with engineering plastic diffuser
- Available in CDL (6500K) & WDL (3000K)
- Available in 14W & 22W



# **LED SPOTLIGHT 2W**

- Designed to fit in compact size
- 2.5 kV voltage surge protection
- Wide operating voltage range 100-300V AC
- Application in cabinets, wall units, etc.
- Available in CDL (6500K), WDL (3000K), red, green & blue
- Available in 2W







# IVORA<sup>®</sup> LED **STRIP LIGHT**

- Used in indirect lighting
- Available in CDL (6500K), WDL (3000K) & blue
- 5 meters long strip light
- Used in home decoration, cove lighting, back lighting, showrooms and shopping malls
- Available in 24W



"Image is for representation purpose only. Actual product may vary. | \*Nearest Incandescent bulb equivalent measure according to IEC 60064, nearest – CFL bulb equivalent measure according to IEC 60969, compared to T8 FTL 36w fitting". | ##Burning life under normal working condition. —



# IVORA<sup>®</sup> LED JUNCTION **BOX DOWNLIGHT**

- Designed to fit in compact size
- 2.5 kV voltage surge protection
- Power factor > 0.9
- Housing made of engineering plastic
- Designed to deliver glare-free light
- Easy installation
- Available in 3W, 6W, New 9W (CDL) & New 12W (CDL)
- Available in CDL (6500K) & WDL (3000K)

# OUTDOOR LUMINAIRES





# **GLISTER LED STREET LIGHT**

- Lumen efficacy of 100 Lm/W
- IP-66 protection
- IK08 protection
- 4 kV voltage surge protection
- Available in CDL (5700K)
- Suitable for outdoor applications in gated communities, periphery lighting, security lighting, general outdoor lighting
- Available in 15W, 20W and 25W

# LED MINI FLOODLIGHT

- IP-65 protection
- Lumen efficacy of 90 Lm/W
- 2.5 kV voltage surge protection
- Power factor > 0.9
- Housing made of die-cast aluminium in glossy black finish
- Available in CDL (6500K)
- Available in 30W



VOLTAGE



WIDE OPERATING ECO-FRIENDLY LIGHT HOURS





<sup>#</sup>Image is for representation purpose only. Actual product may vary. | \*Nearest Incandescent bulb equivalent measure according to IEC 60064, nearest



# PORTABLE LED LIGHTS







#### é 🔿 🤅 $( \bigcirc )$ ķ HEAVY DUTY 6V BATTERY 3 MODE SWITCH

**EMERGENCY LIGHT ELX 36** 

- Double sided illumination facility
- Bright chrome plated reflector • Lighting time of 10-12 hours\*
- Charging indicator
- Neon indicator- ON/OFF switch
- Wall mounting provision
- 6V/4500mAh rechargeable battery



HEAVY DUTY 6V BATTERY

#### **EMERGENCY LIGHT ELX 16**

- Bright chrome plated reflector
- Lighting time of 5-6 hours\*
- Charging indicator
- Compact light weight design
- Wall mounting provision
- 3.7V/2500mAh lithium ion rechargeable battery
- Available in red & blue colour





# **DHYUTI MINI RC** LANTERN

- 360° illumination
- Detachable cap with dual attachment
- 3.7V/1800mAh Lithium ion rechargeable battery\*
- 3 mode switch: strong, medium & low
- Lighting time for:
- Full intensity: up to 3 hours\*
- Intermediate intensity: up to 5 hours\*
- Low intensity: up to 18 hours\*







#Image is for representation purpose only. Actual product may vary. | \*With intermittent use. ----







0

# **LED GLOW 648 LR LANTERN**

- No. of LEDs 48
- Rechargeable 6V/4000 mAh powerful sealed lead acid battery
- Lighting time of up to 24 hours\*
- Long back-up
- Heavy duty battery
- 2 mode glow switch



# SOFTLITE 5W LED **TABLE LAMP**

- 5W LED table lamp
- 3 mode feather touch switch high, medium & low
- Sturdy ABS housing with metal bottom
- Soothing light
- Flexible stem for directional lighting
- Cool day light



# SOFTLITE MINI LED RC **TABLE LAMP**

- Flexible stem for directional light
- 3.7V/1200mAh Lithium ion rechargeable battery
- Unique pen stand for keeping accessories
- Lighting time for:
- Full intensity: up to 4 hours\* - Low intensity: up to 8 hours\*
- Touch switch with 4 intensity selection mode



BACK UP OF LIGHT-WEIGHT 4 HOURS\* LI-ION BATTERY

#### **HYPERION TORCH-CUM** TABLE LAMP

- Adjustable torch head with angular movements
- For table lamp: Self-activation push button
- 3.7V/1200mAh Lithium Ion rechargeable battery
- Lighting for:
- Torch full intensity: up to 4 hours\* - Torch low intensity: up to 14 hours\*
- Table lamp: up to 4 hours\* • For Torch 2 switch mode as high & low
- Inbuilt 2 pin charging port



LIGHT-WEIGHT ECO-FRIENDLY LI-ION BATTERY LIGHT



NEW

# **RAFTAAR MAX**

- Single hi-power LED
- 3.7V/1200mAh Li-ion battery
- Lighting time up to 4 hours\*
- Compatible for charging with B-type micro-USB cable
- 3 mode light switch
- Available in red, black and orange colours







#Image is for representation purpose only. Actual product may vary. | \*With intermittent use. ----



# **RAFTAAR JUMBO**

- Single hi-power LED
- 3.7V/1200mAh Li-ion battery
- Lighting time up to 4 hours\*
- Compatible for charging with B-type micro-USB cable
- 3 mode light switch
- Available in red, black & orange colours





# **RAFTAAR MINI**

- Single hi-power LED
- 3.7V/1200mAh Li-ion battery
- Lighting time up to 4 hours\*
- Compatible for charging with B-type micro-USB cable
- 3 mode light switch
- Available in red, black & orange colours





# DOSTI LED TORCH 3W

- Strong beam suitable for long range directional light
- Single hi-power LED
- 3.7 V/4000 mAh Li-ion battery
- Lighting time up to 14 hours\*
- Durable ABS housing
- With USB charging operation
- 2 mode light switch



\*With intermittent use

#### SMART GLOW CHAMAK RADIUM DB LED TORCH

- Single hi-power LED
- Radium glow body that glows in the dark
- Illuminance at 1 metre: More than 500 lux
- Sling for easy handling
- LED life of 50,000 hours\*





# SMART GLOW 0.5W SLEEK LED TORCH

- Single hi-power LED
- 3 units of AA dry battery free with the torch
- Sleek for easy handling
- 2 mode switch: high & low



SWITC



#### SMART GLOW CHAMAK LED TORCH

- Single hi-power LED
- Illuminance at 1 metre: More than 500 lux
- Sling for easy handling
- LED life up to 50,000 hours\*
- Available in 3 colours: black, red & yellow







# CONVENTIONAL LIGHTING



# FTL



# **T8 FTL 36W**

- Lumen output of 2450 Lm
- Available in CDL (6500K) only





# T12 FTL 40W

Lumen output of 2450 LmAvailable in CDL (6500K) only



# **GLS CLEAR LAMPS**

- Available in 40W, 60W, 100W & 200W
- Lumen output of 415 Lm for 40W, 710 Lm for 60W, 1340 Lm for 100W and 3000 Lm for 200W
- Life span of 1000 hours\*

# **T5 TUBE**

- Lumen output of 2400 Lm for 28W CDL and 1650 Lm for 24W CDL
- Available in CDL (6500K) only
- Available in 24W & 28W



# CONVENTIONAL CONSUMER LUMINAIRES



#### **ECOBOX 28W ELECTRONIC**

- Box type luminaire wired with elegantly designed energy efficient electronic ballast (p.f.>0.90)
- Box luminaire made of pre-coated CRCA sheet
- Suitable for T5 FTL 28W



# **ECOBOX 36/40W ELECTRONIC**

- Box type FTL luminaire wired with elegantly designed energy efficient electronic ballast (p.f.>0.90)
- Box luminaire made of pre-coated CRCA sheet
- Suitable for T8 FTL 36W & T12 FTL 40W



# NUSTAR 36/40W CCB

- VPIT copper ballast
- Suitable for domestic application
- Suitable for T8 FTL 36W & T12 FTL 40W



# SAVELITE SLEEK 36W ELECTRONIC

- Sleek strip type luminaire made of pre-coated CRCA sheet with decorative end caps
- Wired with elegantly designed energy efficient electronic ballast (p.f.>0.90)
- Suitable for T8 FTL 36W

# **E-SAVER LX 36/40W ELECTRONIC**

Energy efficient electronic ballast
Enclosed in elegantly designed ABS housing
Suitable for T8 FTL 36W & T12 FTL 40W
Suitable for domestic applications



# ELECTRICAL ACCESSORIES









#### **SPIKE GUARD WITH USB**

- Power 1440VA
- Current rating for socket 6A, current rating for USB 1A
- Protects the equipment from sudden surge in electric current
- **FIRE RETARDANT** 3 sockets for compatibility with plugs of multiple countries
  - 2 USB ports available for charging
  - Suitable for use in household, offices, shops, restaurants, hospitals & more





NEW



- Power 1500VA
- Current rating for socket: 6A
- Protects the equipment against sudden surge in power supply
- 4 sockets for compatibility with plugs of multiple countries
- Suitable for use in household, offices, shops, restaurants, hospitals & more

2 METRE FIRE RETARDANT WIRE LENGTH CABLE



#### **EXTENSION REEL**

- Power 1500VA
- Current rating for socket: 6A
- One 3-pin international socket & two 2-pin sockets
- Comes with handle for convenience



# **4 WAY MULTIPLUG**

- Power: 1500VA
- Current rating for socket: 6A
- Multiplug operation with two 3-pin international sockets & two 2-pin sockets
- Sleek as mounts on the switch board itself






# IDEAL LIGHTING SOLUTIONS

Our home is a reflection of our personality and the effort and love we put into decorating it. While beams and bricks make the structure, it's the decor and lighting that makes it a home. Just like each one of us, every room too has a personality of its own. It just takes the right kind of lighting to bring out that personality and enhance it.








Living room is the most popular place in a home as that's where we spend most of our time either entertaining or simply sitting back and relaxing. Whether it is movie nights or a small gathering with friends, it is important to have diverse light settings that can adapt the living room to suit the occasion. Our *Ivora LED* **Panel (4000K)** is a great choice for the sitting area while our adjustable *Ivora* LED COB Downlights (3000K) are perfect for highlighting artworks, family photos or simply for reducing the glare on the television. Our *Ivora LED Strip Lights (3000K)*, with their indirect lighting, create the perfect environment for a relaxed evening.





By the virtue of being private, bedrooms call for an atmosphere that's relaxed, calm and peaceful. Our *Ivora LED Panels (4000K)* create the perfect relaxed environment needed by our brains to produce melatonin which aids comfortable sleep. If the bedroom doubles up as a study, then our adorable range of *Softlite and Softlite Mini table lamps* make the perfect choice for focused lighting that helps boost concentration levels.

# BEDROOM



# **KITCHEN**

Kitchen is the heart of a home and by the virtue of being a workspace, it requires lighting that's bright and with a good CRI. Our *Sunshine CRI Plus LED Batten (6500l, CRI>90)* is great for general illumination of the kitchen. Our range of compact *Spotlights (2W)* are ideal for kitchen cabinets as they add to the aesthetic appeal of the kitchen.





# LED INDOOR LUMINAIRES

MODEL NAME	RATED POWER	RATED CCT	RATED LUMINOUS FLUX	CUT OUT SIZE
SUNSHINE CRI PLUS LED DOWNLIGHT	12W	DL (5000K)	1200 Lm	Ø 93 mm
IVORA® PLUS LED PANEL - ROUND	6W	CDL (6500K)	660 Lm	Ø 102 mm
	12W	CDL (6500K)	1320 Lm	Ø 152 mm
	18W	CDL (6500K)	1980 Lm	Ø 206 mm
IVORA <sup>®</sup> PLUS LED PANEL - SQUARE	6W	CDL (6500K)	660 Lm	102 x 102 mm
	12W	CDL (6500K)	1320 Lm	152 x 152 mm
	18W	CDL (6500K)	1980 Lm	206 x 206 mm
IVORA <sup>®</sup> LED COB DOWNLIGHT	3W	CDL (6000K)	240 Lm	Ø 58 mm
		WDL (3000K)	225 Lm	
		CDL (6000K)	600 Lm	Ø 77 mm
	6W	WDL (3000K)	540 Lm	
	014	CDL (6000K)	900 Lm	Ø 93 mm
	9W	WDL (3000K)	810 Lm	
	12W	CDL (6000K)	1200 Lm	Ø 93 mm
		WDL (3000K)	1080 Lm	
	15W	CDL (6000K)	1500 Lm	Ø 107 mm
		WDL (3000K)	1350 Lm	
IVORA <sup>®</sup> LED PANEL - ROUND	3W	CDL (6000K)	195 Lm	Ø 66 mm
		NDL (4000K)	165 Lm	
		WDL (3000K)	165 Lm	
	6W	CDL (6000K)	390 Lm	Ø 103 mm
		NDL (4000K)	360 Lm	
		WDL (3000K)	360 Lm	
	9W	CDL (6000K)	630 Lm	Ø 153 mm
		NDL (4000K)	585 Lm	
		WDL (3000K)	585 Lm	Ø 153 mm
	12W	CDL (6000K)	900 Lm	
		NDL (4000K) WDL (3000K)	840 Lm 780 Lm	
		WDL (3000K)	780 LM	

# FOYER

First impression is the last impression. As foyer is the entry to any home, it is important for it to be not just well-designed but also well-lit and beautiful. Our *Ivora LED Ceiling Light* (3000K) creates the perfect ambience of warmth and class.

IVORA <sup>®</sup> LED PANEL - ROUND	15W	CDL (6000K)	1125 Lm	Ø 153 mm
		NDL (4000K)	1125 Lm	
		WDL (3000K)	1050 Lm	
	18W	CDL (6000K)	1440 Lm	Ø 200 mm
		NDL (4000K)	1350 Lm	
		WDL (3000K)	1260 Lm	
IVORA <sup>®</sup> LED PANEL - SQUARE	3W	CDL (6000K)	195 Lm	66 x 66 mm
		NDL (4000K)	165 Lm	
		WDL (3000K)	165 Lm	
	6W	CDL (6000K)	390 Lm	103 x 103 mm
		NDL (4000K)	360 Lm	
		WDL (3000K)	360 Lm	
	9W	CDL (6000K)	630 Lm	153 x 153 mm
		NDL (4000K)	585 Lm	
		WDL (3000K)	585 Lm	
	12W	CDL (6000K)	900 Lm	153 x 153 mm
		NDL (4000K)	840 Lm	
		WDL (3000K)	780 Lm	
	15W	CDL (6000K)	1125 Lm	153 x 153 mm
		NDL (4000K)	1125 Lm	
		WDL (3000K)	1050 Lm	
	18W	CDL (6000K)	1440 Lm	200 x 200 mm
		NDL (4000K)	1350 Lm	
		WDL (3000K)	1260 Lm	
IVORA <sup>®</sup> JUNCTION BOX D/L	3W	CDL (6500K)	210 Lm	Ø 60 mm
		WDL (3000K)	195 Lm	
	6W	CDL (6500K)	540 Lm	Ø 60 mm
		WDL (3000K)	510 Lm	
	9W	CDL (6500K)	855 Lm	Ø 75 mm
	12W	CDL (6500K)	1140 Lm	Ø 85 mm
BAJAJ LED SPOT LIGHT	3W	CDL (6500K)	90 Lm	
		WDL (3000K)	70 Lm	
		BLUE	NA	Ø 34 mm
		GREEN	NA	
		RED	NA	
IVORA <sup>®</sup> LED CEILING LIGHT	14W	CDL (6500K)	1190 Lm	NA
		WDL (3000K)	1090 Lm	
	22W -	CDL (6500K)	1870 Lm	NA
		WDL (3000K)	1760 Lm	

NOTES: